



Cubitron™ 3
Performance Abrasives




**Produce more.
With less.**

**Heavy Grinding and Cutting
Application Guide**

Featuring:

**3M™ Cubitron™ 3 Performance Abrasives and
Scotch-Brite™ Nonwoven Abrasive Products**



The science of 3M re-engineered Precision-Shaped Grain.



3M Cubitron™ 3 Performance Abrasives

Our latest 3M Precision-Shaped Grain


- Re-engineered precision-shaped ceramic grain using a proprietary breakthrough in grain shape with curved sides. This helps increase productivity and lower overall grinding costs.
- Re-engineered precision-shaped ceramic grain using proprietary breakthroughs in molecular bonded technology.



3M Cubitron™ 2 Performance Abrasives

3M Precision-Shaped Grain

- 3M pioneered the first precision-shaped grain using 3M microreplication technology to form consistent sharp peaks that easily “slice” through metal—cutting cooler, faster, and lasting longer than conventional abrasive grain.




Conventional ceramic abrasive

- Conventional ceramic abrasive grain tends to “plow” through metal, causing heat to build up in the workpiece and abrasive, resulting in a slower cut and shorter abrasive life compared to our latest precision-shaped grain.



3M Precision-Shaped Grain and Nonwoven Abrasives

Combine benefits of two 3M technologies that can clean and finish surfaces without changing material geometry or dimension. You get a product that’s soft enough to reduce defects but wears like iron without sacrificing the smooth feel and control you expect from Scotch-Brite™ Products.



The advantages of our cutting edge abrasive grain technology delivers measurable benefits for our customers.



The transformative power of technology.

Productivity Delivered 

Enhanced Productivity

With a significantly faster cut rate, this technology helps manufacturers to process more parts with smaller workforces, helping boost efficiency and output.

Safety Built In 

Improved Worker Safety

Reduced hand-arm vibration and noise prioritize the well-being of employees, helping employers develop better working conditions.


Sustainably Forward 

Sustainability at the Core

Longer-lasting abrasives and eco-friendly packaging align with the industry’s sustainability objectives, helping to reduce carbon footprints and waste.



Fibre Discs



Breakthroughs in technology are redefining the limits of cut rate and total stock removal, with a focus on prioritising productivity, safety, sustainability and optimizing automation.



3M™ Cubitron™ 3 Fibre Disc 1182C
For carbon steel




3M™ Cubitron™ 3 Fibre Disc 1187C
Includes grinding aid for stainless steel

11-Series Discs & Roloc™			
Grade	36+	60+	80+

- ✓ Beveling
- ✓ Surface Grinding
- ✓ Flame Cut Smoothing
- ✓ Weld Grinding

3M™ Cubitron™ 3 Roloc™ Fibre Discs

Disc buttons are colour-coded when needed to identify its grade, making it easy to select the grade required for different applications from corner or curved surfaces to removing weld splatter on small areas.



CB3 Fibre Disc	Color	Grade
1184F Durable edge	○ White	All*
1184F	● Brown	36+
1182C	● Orange	60+
1187C	● Yellow	80+

1182C, 36+ up to
3X
Faster Initial Cut Rate¹
vs. Competitive High-Quality Grinding Wheel

1182C, 36+ up to
60%
More Life More Speed²
vs. 3M™ Cubitron™ 2 Fibre Disc 982C, 36+

1182C up to
88% Less Vibration Exposure³
70% Less Noise Energy⁴
vs. Competitive High-Quality Grinding Wheel

Scan for more detailed product ordering info



1182C



1187C

Learn about the Full System Advantage on page 11.

Flap Discs



3M™ Cubitron™ 3 Flap Disc 1169F

Ideal for use on carbon steel, stainless steel, and other heat-sensitive alloys

Grade	40+	60+	80+
-------	-----	-----	-----

- ✓ Weld Removal
- ✓ Finishing
- ✓ Blending
- ✓ Deburring
- ✓ Surface Preparation
- ✓ Deburring Edges
- ✓ Weld Preparation
- ✓ Sanding
- ✓ Edge Beveling
- ✓ Weld Grinding

Scan for more detailed product ordering info




Up to **49%** More Material Removed⁵
on carbon steel vs. 3M™ Cubitron™ II Flap Disc 969F

Up to **46%** Faster Sustained Cut Rate⁵
on carbon steel vs. 3M™ Cubitron™ II Flap Disc 969F



Cubitron™ 3
Performance Abrasives



Cut-Off and Grinding Wheels

Using re-engineered Precision-Shaped Grain with new molecular bonding technology and sharp, angular structures that continuously fracture to form sharp points to wear evenly, run cool and optimise mineral breakdown.



3M™ Cubitron™ 3 Cut-Off Wheels

For carbon and stainless steel

Up to
3X More Life⁶

10% More Speed⁶

vs. 3M™ Cubitron™ 2 Cut-Off Wheels

Up to
33%

Less Vibration⁷

vs. Competitive Ceramic Grain Wheels

- ✓ For ultra-fast cutting through sheet metal, metal tubing and more

Scan for more detailed product ordering info



3M™ Cubitron™ 3 Depressed Center Grinding Wheels

For carbon and stainless steel

Designed for exceptional life and speed in heavy-duty grinding applications on stainless steel, mild steel and other specialist alloys.

Up to
50% More Life⁸

14% More Speed⁸

vs. 3M™ Cubitron™ 2 Depressed Center Grinding Wheels

Up to
33%

Less Vibration⁹

vs. Competitive Ceramic Grain Wheels

- ✓ Beveling
- ✓ Surface Grinding
- ✓ Weld Grinding
- ✓ Gouging
- ✓ Flame Cut Smoothing



3M™ Cubitron™ 3 Cut & Grind Wheels

For carbon and stainless steel

Fast and versatile — designed to be used both as a grinding wheel and as a cut-off wheel on stainless steel, mild steel and other specialist alloys.

Up to
5% More Speed¹⁰

vs. 3M™ Cubitron™ 2 Cut & Grind Wheels



Better Balance



More Speed

We've reformulated the product to further improve ergonomics vs. Cubitron™ 2

- ✓ All the combined applications of grinding and cut-off wheels





Surface Conditioning Discs




For surface finishing after heavy grinding.

Contains 3M Precision-Shaped Grain for fast cut and long life.

Expanded grades for a large range of applications.

Balance of conformability and durability.

Bright, vivid colours help to identify easier.



- ✓ Light Grinding
- ✓ Deburring
- ✓ Blending
- ✓ Refining
- ✓ Cleaning
- ✓ Finishing

Scotch-Brite™ Precision Surface Conditioning Discs

Up to	40% More Speed¹¹	Up to	2X More Life¹²
vs. Competitive CRS Discs			

Scan for more detailed product ordering info



3M Precision-Shaped Grain

Grades	VFIN	FIN	MED
	CRS	XCRS	

Attachment Types



Scotch-Brite™ Precision Heavy Duty Surface Conditioning Discs

Grinds and blends in one step.

Fast aggressive cut, long life and consistent finish.


Durable construction resists edge wear.

- ✓ Light Grinding
- ✓ Blending
- ✓ Deburring
- ✓ Edge Break

3M Precision-Shaped Grain

Grades	MED	CRS
	XCRS	XCRS

Attachment Types



Coming Soon!



Safety
Built In

No steel wires or high-impact particles that could injure workers.

Stripping Discs

For cleaning after heavy grinding.

Quickly removes rust, paint, mill scale, coatings from metal and leaves a fine finish.

Silicon carbide mineral cuts aggressively with low sparking.

Maintains workpiece shape.



Scotch-Brite™ Clean and Strip XT Pro Disc

Silicon Carbide Mineral

Grade S XCS

Up to **90% Less Vibration**¹³ | Up to **54% More Speed**¹³
vs. Crimped Wire Cup Brushes

- ✓ Finishing
- ✓ Surface Preparation
- ✓ Light Scale Removal
- ✓ Coating Removal

Scan for more detailed product ordering info



Attachment Types



Roloc™



TN Quick Change



Center Hole



5/8-11

Heavy rust / rust pit removal without leaving divots, ideal for weld refinement and removing weld discoloration.

Aluminum oxide mineral cuts to bare metal quickly.

Resists chunking and loading, and performs well on edges.



Scotch-Brite™ Clean and Strip XT Pro Extra Cut Disc

Aluminum Oxide Mineral

Grade A XCS

- ✓ Cleaning
- ✓ Surface Preparation
- ✓ Finishing



Attachment Types



Roloc™



TN Quick Change



Center Hole



5/8-11

Product Selection by Application



3M™ Cubitron™ 3 Fibre Discs

11-Series



3M™ Fibre Discs

7-Series



Scotch-Brite™ Precision Surface Conditioning Discs

XCRS CRS MED FIN



Scotch-Brite™ Precision Heavy Duty Surface Conditioning Discs

MED CRS XCRS XXCRS

 Flat Weld Grinding 	Substrate	Mild Steel			Stainless Steel		
	Weld Type	Large MIG	Med MIG	Small MIG	Large TIG	Med TIG	Small TIG
	Start Here	1182C 36+	1182C 60+	1182C 80+	1187C 60+	1187C 80+	787C 120+ Precision XCRS
	<p>3M™ Cubitron™ 3 Fibre Disc 11-Series 3M™ Fibre Disc 7-Series Scotch-Brite™ Precision Surface Conditioning Discs</p>		<p>For the ultimate in process speed and stock removal capability</p>				
Pre-Finish Point	1	2	3	4	5	6	

 Surface Grinding 	Substrate	Mild Steel			Stainless Steel		
	Duty	Heavy	Med	Light	Heavy	Med	Light
	Start Here	1182C 36+	1182C 60+	1182C 80+	1187C 60+	1187C 80+	787C 120+ Precision XCRS
	<p>3M™ Cubitron™ 3 Fibre Disc 11-Series 3M™ Fibre Disc 7-Series Scotch-Brite™ Precision Surface Conditioning Discs</p>		<p>For the ultimate in process speed and stock removal capability</p>				
Pre-Finish Point	1	2	3	4	5	6	

Alternatives to Fibre Discs in these applications

While we propose 3M™ Cubitron™ 3 Fibre Discs as the recommended solution for these applications, sometimes a strong preference for Grinding Wheels or Flap Discs remains. This could be due to the greater range of applications they can be used for. 3M™ Cubitron™ 3 Depressed Center Grinding Wheels or 3M™ Cubitron™ 2 Flap Discs are available providing exceptional cut speed and life.



3M™ Cubitron™ 3 Depressed Center Grinding Wheels



3M™ Cubitron™ 3 Flap Disc 1169F

 Finish after Weld/Surface Grinding <p>Following the grinding step with these innovative finishing products in as few as just one extra step.</p>	Mild Steel Pre-Finish Point (Coating Thickness / Ra)	+3 mil / 1.23 Ra	+2 mil / 0.61 Ra	+1.5 mil / 0.5 Ra	
	Start Here	1	Precision XCRS	Rarely required	Rarely required
		2	Precision XCRS	Precision CRS	Precision MED
		3	Rarely required	Precision CRS	Precision MED
	Stainless Steel Pre-Finish Point (Ra)	0.8 Ra	0.6 Ra	0.4 Ra	
	Start Here	4	Precision XCRS	Precision MED	Precision FIN
5			Precision MED	Precision FIN	
6			Precision MED	Precision FIN	

Need more durability?

For outer corners and sharp edges switch to Scotch-Brite™ Precision Heavy Duty in the same grade.



Product Selection by Application



3M™ Cubitron™ 3 Depressed Center Grinding Wheels

Type 27




3M™ Cubitron™ 3 Cut & Grind Wheels

Type 27



Scotch-Brite™ Deburr & Finish Pro Unitized Wheel


9C XCRS+




3M™ Cubitron™ 3 Fibre Discs

11-Series

 <p>Fillet Weld Grinding</p>	Substrate	Mild Steel			Stainless Steel		
	Weld Type	Large MIG	Med MIG	Small MIG	Large TIG	Med TIG	Small TIG
	Recommended	3M™ Cubitron™ 3 Depressed Center Grinding Wheel, Type 27 Benchmark speed and life getting into corners			Scotch-Brite™ Deburr & Finish Pro Unitized Wheel, 9C XCRS+ Aggressive cut with more control and low heat		

 <p>Beveling</p>	Substrate	Mild Steel			Stainless Steel		
	Gauge	Heavy	Med	Light	Heavy	Med	Light
	Start Here	1182C 36+	1182C 60+	1182C 80+	1182C 60+	1182C 60+	1182C 80+
	Alternative	3M™ Cubitron™ 3 Fibre Disc 11-Series For the ultimate in process speed and stock removal capability			3M™ Cubitron™ 3 Depressed Center Grinding Wheel, Type 27 Great speed and life with better application versatility		

 <p>Back Grinding and Gouging</p>	Start Here	3M™ Cubitron™ 3 Depressed Center Grinding Wheel, Type 27 Maximum stock removal speed	Minimum 7 mm gouge channel
	Alternative	3M™ Cubitron™ 3 Cut & Grind Wheel, Type 27 More control	Either 3.2 mm or 4.2 mm gouge channel

 <p>Cutting</p>	 <p>3M™ Cubitron™ 3 Cut-Off Wheel</p> <p>Optimized for</p> <ul style="list-style-type: none"> Carbon Steel Stainless Steel 	Thickness (mm) 4.2 3.2 3.0 2.5 2.0 1.6 1.3 1.0 0.8	Metal Heavy Gauge Thin Sheet	 <p>Type 41 Type 42</p>
		<p>Could the customer increase wheel thickness? Cut rate will still be great, but the extra life will be worth it!</p>		 <p>3M™ Cubitron™ 3 Wheels (Type 42) are ideal for cutting applications with difficult access.</p>



Cubitron™ 3
Performance Abrasives



Get more value from your automation investment.

At 3M, we have a deep understanding of the factors that affect an automated abrasive process. Our 100+ years of abrasive experience and 35+ years of abrasive automation experience is accessible through our Technical Experts, our 17 Global Proof of Concept automation labs, and deployed into how we engineer our products.

Products engineered with automation in mind.



3M™ Cubitron™ 3 Performance Abrasives and Scotch-Brite™ Nonwoven Abrasives elevate product life, cut rate and wear consistency. This enhances processes that are already automated or increases the appeal of automating current manual ones.

Start your journey with 3M.

Download the 3M Automation and Robotics Handbook



Automation Ready



Tools that take it to the next

The new electric grinder is available in 115 mm and 125 mm and fixed or variable speed. Designed with robust components, these grinders are built for durability in the harshest industrial conditions. They're the powerful and long-lasting tools you need to get more done.

3M™ Electric Angle Grinder Features:

- ▶ 1900 W power
- ▶ Available in fixed or variable speeds
- ▶ World class ergonomic design
- ▶ Robust design and components provide durability in industrial conditions
- ▶ Restart protection
- ▶ Adjustable guard
- ▶ Accessories for maximum functionality and flexibility
- ▶ Direct cooling for a long service life
- ▶ Overload protection
- ▶ Kickback control



See the difference when using the full system.



3M Abrasives Customer Story

“ We quickly realised we couldn't afford to use anything else but Cubitron™ 3. ”

Graham Hanks, Production Manager at
Reddish Electroplating

The Challenge

Graham Hanks, Production Manager, needed to find a faster way of removing the topcoat, machine marks, and welds down to sound metal before the chrome plating and subsequent finishing steps could be completed. The substrate they use are particularly hard to grind fast with speed and consistency.

The Solution

With support from a 3M Process Specialist, Graham oversaw a trial of 3M™ Cubitron™ 3 Fibre Discs on the 3M™ 1900W Angle Grinder and 3M™ Cubitron™ 3 Cloth Belts on his existing portable belt machines. The patented grain technology meant that even on these hard to grind substrates, the work got done faster and the scratch pattern left behind was more than good enough to chrome plate and polish to the desired finish specification.

Here's what Graham had to say:

“Tom is one of our most experienced metalworkers and his feedback was critical in our assessment of the trial. Once we saw the significant increase in through-put these products are capable of delivering, without compromising on our commitment to quality, we quickly realised we couldn't afford to use anything else but Cubitron™ 3. We now get twice the work done in half the time and the products are lasting at least twice as long. Cubitron™ 3 has transformed our process and supports our commitment to quality work.”



Up to
60%
↓
Less
Abrasives
Used

Tom Gibson, Experienced Metalworker at
Reddish Electroplating

Sustainability matters to 3M Abrasives.



Sustainable European Abrasive Manufacturers

When you buy from the SEAM value chain, you are helping to build a sustainable future for our industry, for people and for the planet. 3M is a founding member of the SEAM abrasives manufacturers program and aligns to the world's highest standards

of quality, safety and performance in a sustainable environment. We commit to transparency, accountability, innovation and progress. When buying from the SEAM value chain, customers are helping to build themselves a sustainable future.



Find out more at
www.seam.earth

Get the abrasives that get more done at 3M.co.UK/Abrasives

1. Performance testing in a typical weld preparation process; 3M™ Cubitron™ 3 Fibre Disc 1182C, 36+ average compared to the average result of 10 globally selected high-quality competitive type 27 grinding wheels including ceramic grain products, according to independent testing by Fraunhofer Institute, January 2024.
2. The 'total material removed' claim is determined by averaging the amount of metal ground over the entire test method (30 cycles or 30 minutes of grinding). Error bars represent the results with a 95% confidence level.
3. Performance testing in a typical weld preparation process; 3M™ Cubitron™ 3 Fibre disc average compared to the average result of 10 globally selected high-quality competitive type 27 Grinding wheels including ceramic grain products, according to independent testing by Fraunhofer Institute, January 2024.
4. Noise energy operator exposure testing in a typical weld preparation process; Cubitron™ 3 Fibre disc average compared to the average result of 10 globally selected high-quality competitive type 27 Grinding wheels including ceramic grain products, according to independent testing by Fraunhofer Institute, January 2024.
5. Results are based on an automated, 37.5 minute, medium pressure test on 1045 steel using 4.5 inch 40 grit flap discs on a servo motor.
6. Results are based on an automated, cutting of a 3 mm thick 304 stainless steel sheet. Cut-off wheel geometry was T41 125 mm x 16 mm x 22 mm mounted on a 1.5 hp angle grinder with an applied force of 9 lbs. Cut speed was defined by time needed to cut 1 meter of stainless steel. The number of cuts was estimated by the amount of wheel that was used after cutting a distance of 1 meter. End of life is assumed to be 50% of initial wheel mass.
7. Performance testing in a typical weld preparation process or cutting operation; 3M™ Cubitron™ 3 Cut-Off Wheels average compared to the average results of the high-quality competitive ceramic grain competitive wheels tested, according to independent testing, August 2023.
8. Results are based on an automated beveling of 1018 carbon steel bars. Grinding wheel geometry was 115 mm outer diameter mounted on a servo motor with an applied force of 12 lbs. Cut speed was defined by metal removed after 10 minutes of testing life. End of life is assumed to be 50% of the initial wheel mass.
9. Performance testing in a typical weld preparation process or cutting operation; 3M™ Cubitron™ 3 Depressed Center Grinding Wheels average compared to the average results of the high-quality competitive ceramic grain competitive wheels tested, according to independent testing, August 2023.
10. Results are based on an automated beveling of 1018 carbon steel bars. Grinding wheel geometry was 115 mm outer diameter mounted on a servo motor with an applied force of 12 lb. Cut speed was defined by metal removed after 10 minutes of testing. The total material removal was estimated based on the amount of wheel that was used for 10 minutes of testing life. End of life is assumed to be 50% of the initial wheel mass.
11. Based on 3M Internal Testing: CRS 3" discs were tested robotically on 304 series stainless steel for 12 minutes, using a 3" 3M™ Hard Back-Up, part number: 45091. One part is equivalent to 20 g of material removed.
12. Based on 3M internal testing: MED 3" discs were tested robotically on 6061 aluminum until the end of life (end of life is determined to be 50% of the averaged cut rate of the first three minutes) using a 3" 3M™ Hard Back-Up, part number: 45091. One part is equivalent to 20 g of material removed.
13. Hand-arm vibration compared to listed competitor and Scotch-Brite™ Clean and Strip XT Pro Disc, Type 27, according to independent testing by Fraunhofer Institute on October 2021.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. **Disclaimer:** 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and other limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, death, or property damage. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com. **Warranty and Limited Remedy:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M, Scotch-Brite and Cubitron are trademarks of 3M Company. All other trademarks are property of their respective owners.
© 2025, 3M. All rights reserved. 61-5005-0085-7

3M Abrasive Products are for industrial use only.



3M United Kingdom PLC
3M Center
Cain Road
Bracknell
RG12 8HT
Tel: +44 8705 360036
abrasives.uk@mmm.com
3M.co.uk/Abrasives

3M Ireland Limited
The Iveagh Building
The Park
Carrickmines
Dublin 18
Ireland
Tel: +353 1800 303 437